

WESEM



work lamps

176 x 87

CRV1A

*with LED and FF optics
supply voltage: 12V-24V DC*

power of 35W

IP68, IP69K rated

luminous flux 3000 lm

Construction and parameters

Application

Work lamps are used to illuminate working space near vehicles, tractors, slow-moving machines, and any other places where 12V or 24V DC power is available.



General information

The lamps comply with EMC Directive 2004/108/EC and do not emit electromagnetic interference as well as they are resistant to it's influence.

Construction

- module - 10 LEDs, made by Cree
- aluminum radiator
- fixing parts and screws made of Inox steel
- plastic lens
- Deutsch DT 2-pin cap connector (option)
- AMP Faston 250 2-pin cap connector (option)
- cable 0,5 m (option)
- cable 8 m (option)
- switch (option)

Useful parts while installing

Deutsch plug DT06-2S 2-pin
- catalogue No. A.07135

Recommendation

Correct polarity required.

Parameters

Rated power: 35W.
Luminous flux 3000 lm.
Permissible power supply voltage of 12V-24V LED module is 10-34V DC.
Colour temperature: 5700-7000 K.
IP68, IP69K rated.

Mounting methods

They can be installed in an upright or upside down position.

Cat. number	Hella Catal. No.	Luminous flux		Type	Accessories										connector	Application		Packaging / pc				
		3000 lm	4000 lm		LED module 12V-24V	LED module 48V	omega bracket	switch	cable 0,15 m	cable 0,5 m	cable 8 m	cigarette lighter plug	magnetic holder	AMP Faston 250		AMP Superseal 1,5	Deutsch DT	Cap / Pin	Plug / Pin	universal	dedicated	blister pack
CRV1A.49501		*		*	*	*												*				1
CRV1A.49502	1GB996386-031	*		*	*	*				*							*	2		*		1
CRV1A.49506		*		*	*	*										*	2		*			1
CRV1A.49514	1GB996386-001	*		*	*	*										*	2		*			1

